

SPECIFICATION

GASOLINE

A95



PROPERTIES	UNIT	RESULT	TEST METHOD
RON	-	Min 95	ASTM D 2699
MON	-	Min 84	ASTM D 2700
Density@15°C	Kg/m ³	740	ASTM D 4052
DVPE	Kpa	58	ASTM D 232
IBP	°C	40	ASTM D 86
10%	°C	57	ASTM D 86
50%	°C	113	ASTM D 86
90%	°C	143	ASTM D 86
FBP	°C	193	ASTM D 86
Residue	%Vol	1	ASTM D 86
Losses	%Vol	2	ASTM D 86
E70	%Vol	32	EN ISO 3405
E100	%Vol	45	EN ISO 3405
E150	%Vol	91	EN ISO 3405
Oxygen	%mass	1.95	EN 1601
Sulphur	Mg/kg	150	ASTM D 4294
Saturate	%Vol	58	ASTM D 1319
Aromatic	%Vol	35	ASTM D 1319
Olefin	%Vol	2	ASTM D 1319
Benzene	%Vol	0.9	EN 238
Ethanol	%Vol	0.0	EN 1601
Methanol	%Vol	0.0	EN 1601
Oxide stability	Minutes	>960	ISO 7536
Copper strip	Merit	1a	ISO 2160
Existent gum	Mg/100ml	<5	ISO 6246
Water content	ppm	120	EN ISO 12937

The analysis will be customizable & produce able as per buyer's request